



JV190006

**Carbon Steel
Sleeved Packed
Lever Operated
Tank Level Gauge
To Suit
Reflex/Transparent
Glass Gauge Boxes
Top & Bottom Set
Flanged
PN40**



The JV190006 set of gauge cocks are fitted with sleeves which can be adjusted by means of packing nuts as wear necessitates, providing easy and efficient maintenance.

Both the top and bottom fittings have sleeved packed, lever operated valves with a drain cock on the bottom fitting.

Approvals, Features & Benefits

- Sleeve packed for easy maintenance
- Drain cock
- High pressure & temperature duty
- Reflex & plate glass suitability

Pressure & Temperature

Max working pressure:-
40 bar
Temperature range:-
-25°C to 425°C
Saturated Steam:-
245°C @ 36 bar

DN	15	20	25
Sight Gauge Box Pipe Dia.	16	16	16
A	150	150	150
B	45	45	45
C	90	90	90
D	43	43	43
E	115	115	115
F	160	160	160
G	47	47	47
H	193	193	193
Weight Kg	6.1	6.7	7.2

MATERIALS

Body	Carbon Steel (A105N)
Spindle & Plug	Stainless Steel
Packing Sleeves	Graphite

OPTIONAL CENTRE SECTIONS & GLASS



Reflex Glass Centre Section Gauge Boxes

- Carbon steel body
- Type B borosilicate reflex glass (DIN 7081)
- 16mm O.D x 60mm length pipe connectors
- 34mm width
- Size B3 to B9 (can be multiplied)
- Max pressure 40 bar
- Max temperature 239°C
- Spare glass and gaskets available



Transparent Glass Centre Section Gauge Boxes

- Carbon steel body
- Type A borosilicate transparent glass (DIN 7081)
- 16mm O.D x 60mm length pipe connectors
- 30mm width
- Size A5 to A7
- Max pressure 64 bar
- Max temperature 243°C
- Spare glass, micas and gaskets available