



JV360010

Hydraulic Pump Unit Station



The advantage of hydraulic remote control of quick closing valves is that the actuating elements (hand pump units) can be positioned well away from any danger areas and operate completely independently of the supply system on board.

The individual pump units can operate a maximum of six quick closing valves at the same time.

It is recommended that hydraulic pipes with an outside dimension of 8mm and with a wall thickness of 1mm are used.

Features & Benefits

- Compatible with JV360001, JV360002, JV360003 & JV360004 quick closing valves
- Up to six quick closing valves can be connected to each pump unit
- Up to eight pump units can be grouped together

Technical Data

Tank Volume:- 110cm³

Stroke:- 35mm

Volume/Stroke:- 30cm³

Max. Hydraulic Pressure:- 20 Bar

Recommended Mineral Oil HL. HLP according to DIN 51524, viscosity range 15 to 32mm²/s

	A	B	C	D	E	F (1x)	F (2x)	F (3x)	F (4x)	F (5x)	F (6x)	F (7x)	F (8x)
	50	130	430	245	70	50	180	250	320	390	460	530	600
Weight Kg	-	-	-	-	-	3	7.2	10.6	14	17.5	21	24.5	28

MATERIALS

Body	Stainless Steel
Lever	Stainless Steel
Piston	Brass
O-Ring	FPM

OPTIONS

Control Cabinets	LED Indication
------------------	----------------