



## JV370003

**Ductile Iron  
Lever Operated  
Spring Loaded  
Angle Pattern  
Self Closing  
Globe Valve**

**Flanged PN16**  
Others on request



This self closing valve has a spring return mechanism. Used in applications where positive return to the shut-off position is required after the valve is manually opened with the lever.

An optional blocking device to prevent accidental operation is available on request.

This valve is installed so that the medium flows directly over the disc.

### Features & Benefits

- 3.1 certificates available on request
- Mainly used for drainage of fuel diesel tanks
- Optional blocking device
- Spring loaded
- Robust construction

### Pressure & Temperature

Pressure range:-  
PN16 rated

Temperature range:-  
0°C to 90°C

DN	15	20	25	32	40	50	65	80	100
<b>A</b>	90	95	100	105	115	125	145	155	175
<b>B (c/w Blocking Device)</b>	150	155	155	155	185	190	220	215	280
<b>C</b>	115	115	125	130	135	145	160		
<b>D</b>	95	105	115	140	150	165	185	200	220
<b>E</b>	160	160	160	160	160	160	160	16	210
<b>Weight Kg</b>	3.9	4.6	5.4	7.1	9.6	12.5	17.6		

### MATERIALS

<b>Body/Bonnet</b>	Ductile Iron (GGG40)
<b>Disc &amp; Stem</b>	Stainless Steel (X14CrMoS 17)
<b>Spring</b>	Stainless Steel (X10CrNi18-8)
<b>O-Ring</b>	FKM
<b>Seat Ring</b>	Stainless Steel (X12Cr 13)
<b>Hand Lever</b>	Stainless Steel (X5CrNi18-10)
<b>Handwheel</b>	Cast Iron (GG25)